

	T110	T1250	T1254	T1256	T1500	T11200	T11202	T11204	T12000
PART NUMBER	MD26-28	6430250-1	6430250-2	6430250-3	MD50	6431200-1	6431200-3	6431200-6	6432000-1
INPUT VOLTAGE	11 – 40 VDC	20 – 36 VDC	20 – 36 VDC	20 – 36 VDC	20 – 36 VDC	20 – 36 VDC	20 – 36 VDC	20 – 36 VDC	20 – 36 VDC
INPUT CURRENT	1.8A max	10A at 28 VDC input	10A at 28 VDC input	10A at 28 VDC input	20A at 28 VDC input	60A max at 28 VDC input	60A max at 28 VDC input	60A at 28 VDC input	80A at 28 VDC input
OUTPUT VOLTAGE	26 VAC ± 1 VAC	115 VAC ± 3%	115 VAC ± 3%	115 VAC ± 3%, 26 VAC ± 3%	115 VAC ± 3%	115 VAC ± 3%	230 VAC ± 3%	115 VAC ± 3%	115 VAC ± 3%
OUTPUT POWER	10 VA	250 VA	250 VA	250 VA for 115 VAC, 75 VA for 26 VAC	500 VA	1200 VA	1200 VA	1200 VA	2000 VA
OUTPUT FREQUENCY	400 Hz ± 0.5%	60 Hz ± 0.1%	400 Hz ± 0.1%	400 Hz ± 0.1%	60 Hz ± 0.1%	60 Hz ± 0.1%	50 Hz ± 0.1%	400 Hz ± 0.1%	60 Hz ± 0.1%
POWER CONVERSION	Oscillator	Current mode control	Current mode control	Current mode control	Current mode control	Current mode control	Current mode control	Current mode control	Current mode control
OUTPUT WAVEFORM	Single phase, pure sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion	Single phase, true sine wave, < 3% total harmonic distortion
WEIGHT	0.28 lbs (0.13 kg)	2.2 lbs. (1.0 kg)	2.2 lbs. (1.0 kg)	2.6 lbs. (1.18 kg)	3.9 lbs. (1.77 kg)	7.3 lbs. (3.31 kg)	7.3 lbs (3.31 kg)	7.3 lbs. (3.31 kg)	7.7 lbs. (3.49 kg)
DIMENSIONS	1.43" H x 2.75" L x 3.0" W	2.02" H x 6.74" L x 5.94" W	2.02" H x 6.74" L x 5.94" W	2.02" H x 6.74" L x 5.94" W	2.74" H x 8.15" L x 6.34" W	3.46" H x 12" L x 6.32" W	3.46" H x 12" L x 6.32" W	3.46" H x 12" L x 6.32" W	3.46" H x 12" L x 6.32" W
EFFICIENCY	60%	90%	90%	90%	86%	88%	88%	88%	93%
REMOTE CONTROL	None	Remote On/Off	Remote On/Off	Remote On/Off	Remote On/Off	Remote On/Off	Remote On/Off	Remote On/Off	Remote On/Off
PROTECTION	Transient and reverse polarity protected	Input transient, overload, short-circuit protection (up to 150% of rated load without damage) and ground fault interrupter (GFI) protection	Input transient, overload, short-circuit protection (up to 150% of rated load without damage) and ground fault interrupter (GFI) protection	Input transient, overload, short-circuit protection (up to 150% of rated load without damage) and ground fault interrupter (GFI) protection	Input transient, overload and short-circuit protection (up to 150% of rated load without damage)	Input transient, overload and short-circuit protection (up to 150% of rated load without damage)	Input transient, overload and short-circuit protection (up to 150% of rated load without damage)	Input transient, overload and short-circuit protection (up to 150% of rated load without damage)	Input transient, overload and short-circuit protection (up to 150% of rated load without damage)
ALTITUDE	-1,000 to +50,000 feet	55,000 ft	55,000 ft	55,000 ft	55,000 ft	55,000 ft	55,000 ft	55,000 ft	55,000 ft
HUMIDITY	0 to 95% at 25°C	Tested to greater than 95% for 10 days, temperature cycle of 100°F to 150°F	Tested to greater than 95% for 10 days, temperature cycle of 100°F to 150°F	Tested to greater than 95% for 10 days, temperature cycle of 100°F to 150°F	Tested to greater than 95% for 10 days, temperature cycle of 75°F to 160°F	Tested to greater than 95% for 10 days, temperature cycle of 75°F to 160°F	Tested to greater than 95% for 10 days, temperature cycle of 75°F to 160°F	Tested to greater than 95% for 10 days, temperature cycle of 75°F to 160°F	Tested to greater than 95% for 10 days, temperature cycle of 75°F to 160°F
TEMPERATURE	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)	-67°F to +158°F (-55°C to +70°C)
INTEGRAL COOLING	None required	None required	None required	None required	Dual, electronically-controlled brushless fans	Dual, electronically-controlled brushless fans	Dual, electronically-controlled brushless fans	Dual, electronically-controlled brushless fans	Dual, electronically-controlled brushless fans
MATING CONNECTOR	Terminal block	MS3106A-18-9S (MCI P/N 9016905-1,-2)	MS3106A-18-9S (MCI P/N 9016905-1,-2)	MS3106A-18-9S (MCI P/N 9016905-1,-2)	MS3102A-18-9S (MCI P/N 9016905-1,-2)	MS3106A24-12S, MS3057-16A (cable clamp / backshell) (MCI P/N 9017235-1, -2)	MS3106A24-12S MS3057-16A (cable clamp / backshell) (MCI P/N 9017235-1, -2)	MS3106A24-12S MS3057-16A (cable clamp / backshell) (MCI P/N 9017235-1,-2)	9018784-1 9018550-2 (cable clamp / backshell)
MOUNTING	Base mount	Flexible orientation	Flexible orientation	Flexible orientation	Flexible orientation	Flexible orientation	Flexible orientation	Flexible orientation	Flexible orientation
CASE	Anodized aluminum base plate, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue	Anodized aluminum extrusion, blue
CERTIFICATION	FAA PMA approved	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified	FAA TSO-C73 certified RTCA DO-160F qualified	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified	FAA TSO-C73 certified EASA ETSO-C73 certified RTCA DO-160G qualified
WARRANTY	Two-year limited	Two-year limited	Two-year limited	Two-year limited	Two-year limited	Two-year limited	Two-year limited	Two-year limited	Two-year limited