

TRUE BLUE POWER

A division of Mid-Continent Instrument Co., Inc.



Advanced Lithium-ion Battery

TB17

Manufactured by Mid-Continent Instrument Co., Inc.



The TB17 Advanced Lithium-ion Battery uses the most sophisticated lithium-ion chemistry available. providing aviators with an unmatched advantage of power, safety, life and energy.

Ideal for the piston, turbine, and emergency power market, the TB17 starts the aircraft's engine quickly and features superior energy density — Nanophosphate® lithium-ion cells offer 3x the energy per kilogram, resulting in a battery that is 45% lighter than lead-acid or nickel-cadmium alternatives.

This advanced battery system is engineered to deliver an overall lower cost of ownership with a 2-year maintenance schedule, efficient engine starts, extended useful life and intelligent battery status communication to the cockpit.

Product features

CAPACITY

17 amp-hour battery nominal at 23°C/73.4°F

WEIGHT

15.6 lbs.

TECHNOLOGY

Advanced Nanophosphate® lithium-ion cell chemistry from A123 Systems, LLC

EFFICIENCY

Higher voltage during engine start — Less wear, less maintenance and

increased useful life

PERFORMANCE

7 engine starts in 7 minutes

30 minutes (at 34 amps) for complete recharge when the battery is fully

discharged

Superior performance at higher temperatures (up to 50°C/122°F)

ENERGY DENSITY

A123 battery cells deliver 3x the energy per kilogram when compared to lead-acid

and nickel-cadmium cells

INTERNAL HEATER

Automatic internal heater

PROTECTION

Overcharge, over-discharge, over-current, short circuit, over-temperature, undertemperature and charge current limiting

COMMUNICATION

Battery status to the cockpit

MAINTENANCE

2-year maintenance interval; offers 50 – 90% savings on maintenance costs

DESIGNED AND MANUFACTURED Wichita, Kansas, USA

WARRANTY

2-year limited





















Technical specifications

CAPACITY 17 amp-hour battery nominal at 23°C/73.4°F

CHARGE VOLTAGE 28 VDC nominal

OUTPUT VOLTAGE 26.4 VDC nominal

OUTPUT CURRENT 240A continuous, 840A max

TECHNOLOGY Advanced Nanophosphate® lithium-ion cell chemistry from

A123 Systems, LLC

PROTECTION Overcharge, over-discharge, over-current, short circuit, over-temperature, under-

temperature and charge current limiting

ENERGY DENSITY 66.0 Wh/kg

OPERATING 87.1 Wh/liter TEMPERATURE

-40°C to 50°C (-40°F to 122°F)

DIMENSIONS 15.6 lbs

CONFIGURATION 7.22" L x 7.37" W x 6.01" H

MAINTENANCE 7P8S: 7 parallel cells v 8 se

AINTENANCE 7P8S; 7 parallel cells x 8 series modules

2-year maintenance interval; offers 50 – 90% savings on maintenance costs

30 – 30 /0 savings on manitenance cos

Anodized aluminum, blue

FAA TSO certified to C179a ETSO certified to C179a RTCA DO-311 qualified RTCA DO-160G qualified UNDOT/IATA certified

Product comparison

	Battery Technology	Voltage Output	Capacity (1C rate)	Weight	Maintenance	Useful Life
TB17	Lithium-ion	26.4 VDC	17 amp-hour	15.6 lbs.	2 years	6 – 10 years
	Lead-acid	24 VDC	13.6 amp-hour	29.5 lbs.	Annual	2 – 4 years
	Nickel-cadmium	24 VDC	17 amp-hour	38.5 lbs.	200 – 400 hours	5 – 10 years

CASE

CERTIFICATION

