

H3R
AVIATION

Fly
With
Confidence




HALON 1211 FIRE EXTINGUISHERS


- Halon 1211 fire extinguishers offer unmatched fire fighting performance
- Contain Halon 1211 recycled in accordance with the Montreal Protocol
- UL listed and tested to UL 711 and UL 1093
- Pressure gauge enables easy confirmation of charge
- FAA-accepted per FAA Advisory Circular: AC 20-42D




A344T	2B:C Cockpit/Cabin
Agent weight	1.25 lb.
Gross weight	2.3 lb.
Discharge range	9-12 ft.
Discharge time	10 sec.
Height	10.25 in.
Width	3.9 in.
Cylinder diam.	2.6 in.




A344TC	2B:C Cockpit/Cabin
Agent weight	1.25 lb.
Gross weight	2.3 lb.
Discharge range	9-12 ft.
Discharge time	10 sec.
Height	10.25 in.
Width	3.9 in.
Cylinder diam.	2.6 in.




C352TS	5B:C Cockpit/Cabin
Agent weight	2.5 lb.
Gross weight	5.0 lb.
Discharge range	9-15 ft.
Discharge time	10 sec.
Height	14.5 in.
Width	4.5 in.
Cylinder diam.	3.0 in.




C352TSC	5B:C Cockpit/Cabin
Agent weight	2.5 lb.
Gross weight	5.0 lb.
Discharge range	9-15 ft.
Discharge time	10 sec.
Height	14.5 in.
Width	4.5 in.
Cylinder diam.	3.0 in.




C354TS	5B:C Cockpit/Cabin
Agent weight	3.0 lb.
Gross weight	5.6 lb.
Discharge range	9-15 ft.
Discharge time	12 sec.
Height	14.4 in.
Width	6.3 in.
Cylinder diam.	3.0 in.




B355T	10B:C Cockpit/Cabin
Agent weight	5.0 lb.
Gross weight	8.8 lb.
Discharge range	9-15 ft.
Discharge time	10 sec.
Height	15.3 in.
Width	5.8 in.
Cylinder diam.	4.25 in.




B369	10B:C Ramp/Cargo
Agent weight	9.0 lb.
Gross weight	16.75 lb.
Discharge range	12-18 ft.
Discharge time	9 sec.
Height	16.3 in.
Width	8.5 in.
Cylinder diam.	5.0 in.



B371	2A:40B:C Ramp/Cargo
Agent weight	13.0 lb.
Gross weight	22.1 lb.
Discharge range	12-18 ft.
Discharge time	14 sec.
Height	20.3 in.
Width	8.5 in.
Cylinder diam.	5.0 in.



361	4A:80B:C Ramp/Cargo
Agent weight	17.0 lb.
Gross weight	34.8 lb.
Discharge range	12-18 ft.
Discharge time	22 sec.
Height	23.9 in.
Width	9.8 in.
Cylinder diam.	7.0 in.




HALON ALTERNATIVE FIRE EXTINGUISHERS

HALOTRON® 1


- The most widely deployed and the least expensive Halon 1211 alternative
- UL listed and tested to UL2129 & UL711




A384T	1B:C Cockpit/Cabin
Agent weight	1.4 lb.
Gross weight	2.6 lb.
Discharge range	6-8 ft.
Discharge time	9 sec.
Height	10 in.
Width	3.5 in.
Cylinder diam.	2.6 in.




B385TS	2B:C Cockpit/Cabin
Agent weight	2.5 lb.
Gross weight	5.4 lb.
Discharge range	6-10 ft.
Discharge time	9 sec.
Height	14.8 in.
Width	5.0 in.
Cylinder diam.	3.0 in.




B394TS	5B:C Cockpit/Cabin
Agent weight	5.5 lb.
Gross weight	9.3 lb.
Discharge range	9-15 ft.
Discharge time	9 sec.
Height	15.0 in.
Width	5.13 in.
Cylinder diam.	4.25 in.



397	1A:10B:C Ramp/Cargo
Agent weight	11 lb.
Gross weight	22.5 lb.
Discharge range	9-15 ft.
Discharge time	9 sec.
Height	21.9 in.
Width	9.25 in.
Cylinder diam.	6.0 in.



398	2A:10B:C Ramp/Cargo
Agent weight	15.5 lb.
Gross weight	27.5 lb.
Discharge range	12-18 ft.
Discharge time	14 sec.
Height	21.9 in.
Width	9.25 in.
Cylinder diam.	6.0 in.




HALOTRON® BRX


- The smallest, lightest and the most effective Halon 1211 alternative
- UL listed and tested to UL2129 & UL711




337TS	2:BC Cockpit/Cabin
Agent weight	1.92 lb.
Gross weight	3.18 lb.
Discharge range	7-8 ft.
Discharge time	9 sec.
Height	11.25 in.
Width	4.0 in.
Cylinder diam.	3.25 in.




347TS	5:BC Cockpit/Cabin
Agent weight	3.75 lb.
Gross weight	5.5 lb.
Discharge range	10-12 ft.
Discharge time	9 sec.
Height	17.6 in.
Width	4.0 in.
Cylinder diam.	3.25 in.



349TS	5:BC Cockpit/Cabin
Agent weight	3.75 lb.
Gross weight	5.75 lb.
Discharge range	10-12 ft.
Discharge time	9 sec.
Height	17.6 in.
Width	5.9 in.
Cylinder diam.	3.25 in.



351	2A:10:BC Ramp/Cargo
Agent weight	12.5 lb.
Gross weight	19.88 lb.
Discharge range	15-17 ft.
Discharge time	16 sec.
Height	20.25 in.
Width	8.5 in.
Cylinder diam.	5.0 in.



WHEELED EXTINGUISHERS

Wheeled fire extinguishers offer outstanding fire stopping power in a convenient towable package optimized for on-demand flight line protection.

HALOTRON® 1

- Most popular wheeled flight line extinguishers
- Can be found at airports throughout the world
- Low Global Warming Potential (GWP)
- Low Ozone Depletion Potential (ODP)
- Short atmospheric lifetime



B673

4A:80B:C

Agent weight	65.0 lb.
Gross weight	286.0 lb.
Discharge range	30-45 ft.
Discharge time	22 sec.
Height	58.0 in.
Width	28.0 in.
Depth	39.0 in.



B674

10A:120B:C

Agent weight	150.0 lb.
Gross weight	512.0 lb.
Discharge range	30-45 ft.
Discharge time	38 sec.
Height	64.0 in.
Width	30.0 in.
Depth	42.0 in.



NOVEC™ 1230

- Zero ozone depletion potential (ODP)
- 5-day atmospheric lifetime (vs. 65 years for halons)
- Global warming potential of 1 (similar to naturally-occurring CO2)
- No regulations or phase-down measures globally



775

3A:80B:C

Agent weight	150.0 lb.
Gross weight	395.0 lb.
Discharge range	30 ft.
Discharge time	22 sec.
Height	59.0 in.
Width	29.0 in.
Depth	42.0 in.



MOUNTING OPTIONS

FAA DAR Tested Bracket

- **Model BKT325** fits H3R Aviation fire extinguisher models 347TS and 349TS and Kidde Technologies fire extinguisher model 476288
- Successfully tested to the requirements defined in Title 14 CFR Part 23, 25, 27 and 29



Box-type Brackets

- **Model 809** fits B369, B371 and 351 fire extinguishers
- **Model 810** fits model 361 fire extinguisher
- **Model 812** fits 397 and 398 fire extinguishers



Extreme Duty Brackets

- **Not certified** for use on aircraft - experimental aircraft only
- **Model NB300** fits C352TS/C, C354TS and B385TS/C
- **Model NB350** fits model P3APP003010A
- **Model NB425** fits B355T & B394TS
- **Model NB500** fits B369, B371 & 351

